



Lubricants



WRAS Approved

SILICONE LUBRICANT

GENERAL PURPOSE SILICONE LUBRICANT

Silicone Lubricant is a general purpose, medium duty silicone lubricant, which exhibits excellent anti-stick and slip properties.

Ideal for use where a clean, colourless lubricant is required. Safe to use on wood, glass, fabrics, metals, most plastics, rubbers and hard surfaces.

PRODUCT CODES / FILL SIZES



31631 / 500ml

APPLICATIONS

- Sewing Machines
- Cutting Table
- Processing Equipment
- Laying-up Areas
- Cutting Knives
- Blades and Guillotines
- Foam Conversion
- Chutes and Conveyors
- Paper and Textile
- Anywhere that sticking or fusing causes problems
- Can also be used as a mould release agent

DIRECTIONS

- Apply a light, even coating from 9" - 12" (25 - 30 cm).
- Remove any overspray with a clean cloth.
- Re-apply as necessary.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, colourless liquid
Odour	Hydrocarbon solvent
SG @ 25°C	0.709
Pressure @ 25°C	3.5 Bar
Discharge rate	0.9 g/sec
Temperature range	Operational from -50°C to +200°C
Solubility	Soluble in solvents, insoluble in water
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

MATERIALS COMPATIBILITY

OK	Wood, glass, fabrics, metals, most plastics, rubbers and hard surfaces
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

